



MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE

Not classified as hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company: *Wynn's Australia Pty. Limited*
Address: *1 Rodborough Road, Frenchs Forest N.S.W. 2086.
P.O. Box 6096, Frenchs Forest N.S.W. 1640.*
Telephone Number: *(02) 9451 3444*
Emergency Telephone Number: *None Available*
Fax Number: *(02) 9975 1785*
E-Mail: *wynnsaus@wynns.net*

IDENTIFICATION

Product Name: *Wynn's Supreme Engine Oil Stop-Leak*
Other Names: *None allocated*
Manufacturer's Product Code: *50606 350ml*
UN Number: *None allocated*
Dangerous Goods Class and Subsidiary Risk: *None allocated*
Hazchem Code: *None allocated*
Poisons Schedule Number: *None allocated*
Use: *A mineral oil based engine seal conditioner*
Packaging Group: *None allocated*

Physical Description/Properties

Appearance: *Clear amber thick liquid*
Boiling Point (°C): *>288*
Vapour Pressure (pascals or mm of Hg at 25°C): *Not available*
Specific Gravity: *0.87*
Flash Point (°C): *196 (ASTM D92)*
Flammability Limits (%): *Not available*
Solubility in Water (g/L): *Nil*

Other Properties:

Volatiles (%): Nil
Freeze Point (°C): -12

Ingredients

<u>Chemical Entity:</u>	<u>CAS Number:</u>	<u>Proportion:</u>
<i>organo seal swell agent</i>		<10%
<i>ethylene propylene copolymer</i>		<10%
<i>petroleum oil</i>	[64741-96-4]	30 - 60%
<i>petroleum oil</i>	[64742-54-7]	30 - 60%

HEALTH HAZARD INFORMATION

Health Effects

Acute

- Swallowed: *If swallowed, may cause slight irritation to digestive tract.*
- Eye: *May be slightly irritating to the eyes on direct contact.*
- Skin: *Can cause irritation to skin. Prolonged contact causes redness, defatting of skin to sensitive individuals.*
- Inhaled: *Vapours generated at elevated temperatures can cause irritation to respiratory tract.*
- Chronic *Prolonged and repeated contact with skin and eyes will cause skin and eye irritation, defatting of skin and redness.*

First Aid

- Swallowed: *Do not induce vomiting. Give 2-3 cups of water or milk. Call for medical help.*
- Eye: *Flush eyes with water for 15 minutes. If irritation persists, call for medical help.*
- Skin: *Wash affected area with soap and water. If irritation persists, call for medical help.*
- Inhaled: *Remove to fresh air to avoid further inhalation.*
- First Aid Facilities: *Eye wash station.*

Advice to Doctor: *Treatment should be controlled by symptoms and clinical conditions. Emesis may be induced under medical supervision.*

PRECAUTIONS FOR USE

- Exposure Standards: *Threshold Limit Value (TLV): 5mg/m³ as Mist (Petroleum Oil). OSHA PEL. ACGIH TLV-TWA.*
- Engineering Controls: *Use in a normal ventilated area. If misting occurs, a mechanical or local exhaust is recommended.*
- Personal Protection: *Wear impervious gloves and suitable eye protection. Personal cleanliness is always appropriate. Frequent washing minimizes inadvertent exposure.*
- Glove Type: *PVC or Nitrile gloves. Rubber, plastic gloves.*
- Eye Protection: *Industrial safety glasses or chemical goggles.*
- Flammability: *Not flammable under conditions of use. Combustible.*

SAFE HANDLING INFORMATION

- Storage and Transport: *Store in cool dry place. Keep containers closed. Keep away from heat and open flame. No special transport requirements necessary. Keep out of reach of children.*
- Spills and Disposal: *Contain liquid with absorbent sand or clay. Shovel into waste containers. For large spills, vacuum track and dispose of properly in accordance with Federal, State and Local requirements. Keep liquid out of sewers and storm water.*
- Fire/Explosion Hazard: *Avoid heat, open flame, strong oxidizing agents. Combustion will produce smoke and toxic fumes. Thermal decomposition may produce oxides of carbon, sulphur and nitrogen. Water may be used to keep fire-exposed containers cool. Fire fighters should wear a self-contained breathing apparatus as combustion can produce toxic fumes of carbon monoxide gas. Dry chemicals, carbon dioxide, water spray, or foam are recommended as extinguishing media. Handle as petroleum mineral oil. Combustible. Non-flammable.*

OTHER INFORMATION

This material has not been identified as a carcinogen by NTP, IARC or OSHA. Contains no other ingredients now known to be hazardous as defined by OSHA 29CFR 1910.1000(z) and 29CFR 1910.1200.

CONTACT POINT

*Technical Sales Manager (business hours)
Wynn's Australia Pty Ltd (02) 9451 3444*

Poisons Information Centre (24 hours) 131126

Note: This form has been prepared in accordance with WORKSAFE AUSTRALIA NATIONAL CODE OF PRACTICE FOR THE PREPARATION OF MATERIAL SAFETY DATA SHEETS [NOHSC:2011 (1994)] issued by the NATIONAL OCCUPATION HEALTH AND SAFETY COMMISSION MARCH 1994.

All information contained in this form is as accurate as possible at the time of issue. The data contained herein is not to be taken as an expressed or implied warranty or representation, for which Wynn's Australia Pty Ltd assumes legal responsibility. No responsibility for damages resulting from use of the information are given, other than those implied mandatorily by Federal or State Government Legislation.